

Nice MoonLight



Flashing signal light.

Available with different power supply voltages:
230 Vac, 24 Vdc and 12 Vdc.

Practical: suitable for mounting in any position.

Incorporated 433.92 MHz aerial on all versions.

IP44 protection level.

Available in two colours: orange and neutral.

MLL version, ideal for 230 V control units without provision, connected directly to the power line, this product monitors absorption and is activated automatically when the automation starts to operate.

Dual function: programmable in flashing light or courtesy light mode.

Flashing light: activated when an automation manoeuvre is in progress.

Courtesy light: activated when the automation starts to operate and, thanks to the internal timer, remains activated for a programmable time interval.



Code	Description	Pc/Pack
ML	Orange, 230 Vac, for preset control units	1
MLT	Neutral, 230 Vac, for preset control units	1
ML24	Orange, 24 Vac/Vdc, for preset control units	1
ML24T	Neutral, 24 Vac/Vdc, for preset control units	1
MLB	Orange, 12 Vac/Vdc, for preset control units	1
MLBT	Neutral, 12 Vac/Vdc, for preset control units	1
MLL	Neutral, 230 Vac, for non preset control units. Supplied with one white lamp and one orange lamp	1

Compatibility table	A0	A0R	A1	A100F	A02	A3	A3F	A400	A500	A6	A6F	A60	A700F	A824	A924	MC824H	MC424L	WALKY	POP	POP7124	HYKE	ROBO 230 Vac	ROBO 24 Vdc	ROAD	ROBUS	RUN	THOR / THOR-Q	TUB	SPIN / SPINBUS	SPIDER / SPIDO	TEN	OTTO 230 Vac	OTTO 24 Vdc	CLIMBER	SOON	X-BAR	SIGNO	WIL							
ML / MLT	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
ML24 / ML24T																																													
MLB / MLBT																																													