Nice NiceWay

NRC

Modular control system

to manage the range of Nice automations, such as awnings, rolling shutters, gates and garage doors, from any point within the home.



1. The transmitter module 2. The module holder cover 3. Wall or table shockproof holder 4. Table shockproof holder 5. Squared wall plate 6. Rectangular wall plate.

Technical specifications

| recillical specifications | | |
|--------------------------------------|---------------------------------------|--|
| Power supply (Vdc) | : 3 V with 1 lithium battery CR2032 | |
| Battery life | : > 2 years with 10 events/day | |
| Frequency | : 433.92 MHz ± 100 KHz | |
| Radiated power | : estimated at approx. 1 mW | |
| Protection rating (IP) | : 40 | |
| Estimated range | : 200 m in a free field, 35 m indoors | |
| Coding | : 52 Bit rolling code | |
| Operating temperature (°C Min. Max.) | : -20 ÷ +55 | |
| Dimensions (mm) | : 41x41x10 | |
| Weight (g) | : 14 | |

Modular

The NiceWay system is based on a number of transmitter modules that can be placed in five different holder models to create a flexible range of made-to-measure solutions. Although the modules, available from 1 to 80 groups or 240 channels, are very small in size, they are extremely easy to operate.

Advanced and compatible

Frequency of 433.92 MHz, 52 Bit Rolling Code with (over 4.5 million of billion combinations); self-learning function.

Compatible with the 433.92 MHz Nice Ergo, Plano, FloR and VeryVR systems (Flo and Smilo with WM240C and WM080G).

Estimated range: 200 m in a free field, 35 m indoors. Extended battery life (3 V lithium battery).

All the NiceWay solutions

The 240 channel module with display, which controls 80 groups and 70 multi-groups, is ideal for the management of sophisticated systems. All the awnings, roller shutters and gates, as well as the office, home and hotel irrigation and lighting systems in just 14 g and 16 cm²!

Made-to-measure

To protect the electronic parts from dirt and damp, the rubber function buttons are incorporated in the actual body of the control modules.

NiceWay can be used anywhere in the home, in the garage, the living room, the kitchen as well as the bathroom.

Professional

For a more professional and practical use, the system can be programmed by means of the handy Nice palmtops.

Nice Design

Sophisticated shock-proof materials, immaculate finish, and essential design: wear, comfort and ease are guaranteed by the internationally renowned and prize-winning Nice design.

The choice of discreet or personalised solutions is vast thanks to the wide choice of colours and finishes.

The heart of the NiceWay system

The 1, 3, 6 and 9-channel modules for the control of single automations, groups or multi-groups: awnings, roller shutters, rolling doors, gates, industrial and garage doors, barrier gate operators, lighting and irrigation systems.

Modules to control Step-by-Step automation systems

| Module | Code | Description | Pc/Pack |
|--------|--------|---|---------|
| | WM001C | Single channel module to control 1 automation system | 10 |
| | WM003C | Three channel module to control 3 Step-by-Step automation systems | 1 |
| 0000 | WM009C | Nine channel module to control 9 Step-by-Step automation systems | 1 |

Memorizing radio controls in Mode I: ON - OFF Mode II: ON/OFF - HOLD TO RUN - TIMER1 - TIMER2 (for the Screen products MODO II programmation)

Hybrid module to control Step-by-Step and Open-Stop-Close automation systems

| Module | Code | Description | Pc/Pack |
|--------|----------|---|---------|
| 000 | WM003C1G | Module to control 3 Step-by-Step and 1 Open-Stop-Close automation systems | 1 |

Modules to control Open-Stop-Close automation systems

| Module | Code | Description | Pc/Pack | |
|--------|--------|---|---------|--|
| | WM001G | Module to control 1 Open-Stop-Close automation system either individually or in multi-group mode | 1 | |
| 900 | WM002G | Module to control 2 Open-Stop-Close automation systems either individually or in multi-group mode | 1 | |
| 0000 | WM003G | Module to control 3 Open-Stop-Close automation systems either individually or in multi-group mode | 1 | |
| 90000 | WM006G | Module to control 6 Open-Stop-Close automation systems either individually or in multi-group mode | 1 | |
| 9000 | WM004G | Module to control 4 Open-Stop-Close automation systems either individually or in multi-group mode and sun sensor activation command | 1 | |

Multi-channel display module

| Module | Code | Description | Pc/Pack | |
|--------|--------|--|---------|--|
| 000 | WM080G | Module to control 80 Open-Stop-Close automation systems either individually or in multi-group mode and sun sensor activation command | 1 | |
| 000 | WM240C | Module to control 240 Step-by-Step automation systems either individually or in multi-group mode | 1 | |